

PRODUCT INFORMATION

REGUPOL EVERROLL VITALITY



Product:

resilient floor covering made of PUR-bonded SBR-granulates, with 50 % EPDM colour content

Areas of Application:

Cardio & machine training, Free weight training & weight-lifting, Indoor cycling, Trampoline parks*

Features:

comfortable, robust, durable, sustainable, non-slip

Standard Roll Dimensions:

Width: 1,250 mm

Length: 10m, 15m, 20m

Thicknesses: 4 mm, 6 mm, 8 mm, 10 mm, 12 mm

Weight:

approx. 1.18 kg/m²/mm

Standard Dimensions Puzzle Tiles:

Outer dimensions: 600 x 600 mm



Thickness: 6 mm

Slip Resistance:

R 10 based on DIN 51130 (02.2014) and ASR A1.5/1,2

Impact Resistance:

> 21 Nm based on EN 14904 / EN 1517



Force Reduction:

up to 15 % based on EN 14904 / EN 14808

Impact Sound Reduction:

Testing based on DIN EN ISO 10140,

REGUPOL everroll classic 8 mm = 19 dB

Fire Classification:

D_{f1} s1 based on EN 13501-1:2010-01 / EN9239-1:2010-11

at **REGUPOL everroll vitality**, 4 mm


Colours:

approx. four standard colours, individual colours available on request


Further technical data is available on request.




REGUPOL everroll vitality EDITION 4.0




Berlin [3116]



Nome [3115]



Goa [3111]



Kush [3112]

Edition 4.0 = brilliant colours and nonreflecting surface

Deviations from the colours shown are possible due to production batches and brochure print.

We reserve the right to make changes to the technical data. The test results and specified values are subject to a tolerance of +/- 10 %. Crucial for the up-to-date data is the information on our homepage www.regupol.com.

*Wherever direct, prolonged or repeated skin contact can be expected, the requirements for a Consumer Product currently valid within the EU must be met. Where this is not expected, your choice can be made from the entire decor portfolio. Those product fulfilling the requirements of a "Consumer Product", are explicitly marked as such. Should any questions arise that need clarification, contact your sales representative at our company directly or write to us using the contact form on our website www.regupol.com.